



GPM Mission Overview

Amita Mehta

2 December 2017

Learning Objectives

- Understand the basics of remote sensing of precipitation
- Identify NASA satellites and sensors used for deriving precipitation
 - describe precipitation data available from these sensors
 - describe data used to track below and above normal precipitation


Presentation Outline

- Precipitation Remote Sensing
- NASA Precipitation Missions and Data
 - Global Precipitation Measurements (GPM) Mission and Tropical Rainfall Measuring Mission (TRMM)
- TRMM and GPM Data Products
- TRMM/GPM Data Access and Visualization
 - Demonstration Precipitation Processing System STORM
 - Demonstration of Giovanni




Spectral Bands Used for Precipitation Remote Sensing

- Derived from:
 - reflected visible radiation (0.5 to 0.6 micrometer wavelength)
 - emitted infrared radiation (10-12 micrometer wavelength)
 - emitted microwave radiation (10 to 183 Ghz frequency or mm to cm wavelength)



Passive Remote Sensing: Inferred indirectly from emitted infrared (IR) radiation by clouds






Image Credit (Left): UCAR COMET, comet.ucar.edu



Passive Remote Sensing: Inferred indirectly from reflected solar visible (VIS) radiation by clouds





Image Credit (Left): UCAR COMET, comet.ucar.edu

Passive Remote Sensing: Estimated from microwave radiation emitted or scattered by precipitation particles



- The lower frequencies, referred to as "emissions channels," measure precipitation mainly from energy emitted by raindrops (37 GHz)
- The higher frequencies, or "scattering channels," gather energy scattered by ice particles above the freezing level (85 GHz)


Image Credit (Left): UCAR COMET, comet.ucar.edu

Active Remote Sensing: Estimated from back-scattered microwave radiation transmitted by radars



Active Instruments emit their own signal and the sensor measures what is reflected back.

Sonar and radar are examples of active sensors.



- NASA Satellites TRMM and GPM use K-band radar
- K-band generally has a frequency range within 27-40 GHz and 12-18 GHz

Image Credit: Paul Messina, Hunter College



NASA Precipitation Missions and Data

GPM and TRMM

http://pmm.nasa.gov/

Dedicated Missions to measure rainfall from active and passive microwave observations:

- Predecessor to Global Precipitation Measurement (GPM) Mission
- Tropical Rainfall Measurement Mission (TRMM)*

*TRMM is no longer available, but very important for long-term rainfall data




TRMM Sensors

http://trmm.gsfc.nasa.gov/

- In a non-polar, low-inclination orbit
- Altitude of approximately 350 km, raised to 403 km after August 23, 2001
- Spatial Coverage
 - 16 TRMM orbits a day covering global tropics between 35°S – 35°N latitude

TRMM Orbits




TRMM Sensors

http://trmm.gsfc.nasa.gov/

- Sensors:
 - TRMM Microwave Imager (TMI)
 - Precipitation Radar (PR)
 - Visible and Infrared Scanner (VIRS)
 - Lightening Imaging Sensor (LIS)
 - Clouds and the Earth's Radiant Energy System (CERES)

TRMM Orbits




TRMM Microwave Imager (TMI)

http://pmm.nasa.gov/TRMM/TMI

- Spatial Coverage and Resolution:
 - Coverage: -180° 180°, 35°S –35°N
 - Swath: 760 km (878 km after 8/2001)
 - Vertical Resolution:
 - 0.5 km from surface 4 km
 - 1.0 km from 4-6 km
 - 2.0 km from 6-10 km
 - 4.0 km from 10-18 km

TMI Swaths




2008/05/31 image contains 16 orbits, orbit numbers from 60054 to 60069

TRMM Microwave Imager (TMI)

http://pmm.nasa.gov/TRMM/TMI

- Temporal Coverage and Resolution:
 - November 27, 1998 April 15, 2014
 - 16 orbits per day
- Chanel Frequencies
 - 10.7, 19.4, 21.3, 37, 85.5 GHz

TMI Swaths




2008/05/31 image contains 16 orbits, orbit numbers from 60054 to 60069

Precipitation Radar (PR)

http://pmm.nasa.gov/TRMM/PR/

- Spatial Coverage and Resolution:
 - Coverage: 35°S 35°N
 - Swath: 215 km (247 after 8/2001)
 - Spatial Resolution: 4.3 km (5 km)
 - Vertical Resolution: 250 m (from 0-20 km)
- Temporal Coverage and Resolution:
 - November 27, 1998 October 7, 2014
 - -~16 orbits per day
- Frequency:
 - 13.6 GHz


PR Swaths



GPM Satellite & Sensors

http://pmm.nasa.gov/GPM/

- Core satellite launched Feb 27, 2014
 - in a non-polar, low inclination orbit
 - Altitude: 407 km
- Spatial Coverage
 - 16 day orbits a day, covering global area between 65°S – 65°N
- Along with constellation of satellites, GPM has a revisit time of 2-4 hrs over land
- Sensors
 - GMI (GPM Microwave Imager)
 - DPR (Dual Precipitation Radar)




GPM Microwave Imager (GMI)

http://pmm.nasa.gov/GPM/flight-project/GMI/

- Spatial Coverage and Resolution:
 - Coverage: -180°-180°, 65°S 65°N
 - Swath: 885 km
- Spatial Resolution: 4.4-32 km
- Vertical Resolution:
 - 0.5 km from surface 4 km
 - 1.0 km from 4-6 km
 - -2.0 km from 6-10 km
 - 4.0 km from 10-18 km

GMI Swath




GPM Microwave Imager (GMI)

http://pmm.nasa.gov/GPM/flight-project/GMI/

- Temporal Coverage and Resolution
 - Feb 2014 present, ~2-4 hr observations
- Channel Frequencies
 - 10.6, 18.7, 23.8, 36.5, 89, 166, 183 GHz

GMI Swath




Dual Precipitation Radar (DPR)

http://pmm.nasa.gov/GPM/flight-project/DPR/


- Spatial Coverage and Resolution:
 - Coverage: -180°-180°, 65°S-65°N
 - Swath: 120km (Ka) and 245km (Ku)
 - Spatial Resolution: 5.2km
 - Vertical Resolution: 250m (from 0-20km)
- Temporal Coverage and Resolution:
 - Feb 27, 2014 present
 - $\sim 2-4$ hr observations
- Frequency:
 - 13.6 and 35.5 GHz

DPR Swaths


Ka 35.5 GHZ



Ku 13.6 GHZ



TRMM and **GPM** Comparison



- TRMM measurements are limited to the tropics
- GPM measurements span middle and high latitudes

- GMI & DPR
 - provide improved reference standards for inter-calibration of constellation precipitation measurements
 - better accuracy measurements
- GMI has a higher spatial resolution than TMI
- Improved light rain and snow detection in GMP
- DPR has better identification of liquid, ice, mixed-phase precipitation particles

Importance of TRMM Data Products

- TRMM provided high resolution precipitation data for 17 years
 - Useful for detecting and understanding climate variability and change
- Many applications are developed from TRMM data and still have to transition to using GPM data
 - extreme rain, flood, and drought monitoring and mapping
 - agriculture
 - Health

TRMM and GPM data will be inter-calibrated to provide a combined long-term precipitation record in 2018

Precipitation Algorithms for TRMM and GPM

http://pmm.nasa.gov/science/precipitation-algorithms

There are four major algorithms used to obtain precipitation estimates from GPM/TRMM observations:

- 1. Radar Algorithms
- 2. Radiometer Algorithms
- 3. Combined Radar + Radiometer Algorithms
- 4. Multi-Satellite Algorithms
 - TRMM and GPM Core are used as calibrators for multiple national and international constellation satellites

Summary of TRMM Level-2 Precipitation Products

| Sensor or Product Name | Spatial Resolution & Coverage | Temporal Resolution | Data Format |
|---------------------------|--|--|----------------|
| PR only: 2A25 | 5 km x 5 kmSingle orbit16 orbits/day (35°S–35°N) | 7-day latency for near real-time 3-hour, 2-day, 5-day | |
| TMI only: 2A12 | 5 km x 5kmOrbital16 orbits/day (38°S–38°N) | • 3-hour, 2-day, 15-day | HDF4 |
| Combined TMI & PR: 2B31 | 5 km x 5 kmOrbital16 orbits/day (38°S–38°N) | 7-day latency for near real-time 3-hour, 2-day, 5-day | |

Summary of TRMM Level-3 Precipitation Products

| Sensor or Product Name | Spatial Resolution & Coverage | Temporal Resolution | Data Format |
|---------------------------|---|--|--|
| TMPA: 3B42RT & Final 3B42 | • 0.25°×0.25° | RT is NRT with 8 hr latency3-hourly | RT data in binary and OpenDAP |
| TMPA: 3B43 | • 50°S×50°N | Monthly2 month latency | HDF4NetCDF |
| PR only: 3A12 | 0.5°×0.5° and 5°×5°37°S×37°N | • Monthly | |
| TMI only: 3A12 | • 0.5°×0.5° • 38°S×38°N | • Monthly | HDF4OpenDAP |
| TMI-PR Combined: 3B31 | • 5°×5° • 40°S×40°N | • Monthly | |

Summary of GPM Level-2 Precipitation Products

| Sensor or Product Name | Spatial Resolution & Coverage | Temporal Resolution | Data Format |
|-------------------------|---|------------------------|--|
| DPR Ku-only: 2A-Ku | • 5.2 km x 125 m | • 20-120 | |
| DPR Ka-only: 2A-Ka | • Single orbit | minutes • 24 hrs | |
| DPR Ku & Ka: 2A-DPR | 16 orbits/day (70°S-70°N) | | |
| GMI/2A-GPROF | 4 km x 4 kmOrbital16 orbits/day (70°S-70°N) | • 2-40 hrs | HDF5OpenDAP |
| Combined GMI+DPR:2A-CMB | 5 km x 5 km Orbital (70°S-70°N) Coincident Ku-Ka GMI footprints | • 3-40 hrs | |

Summary of GPM Level-3 Precipitation Products

| Sensor or Product Name | Spatial Resolution & Coverage | Temporal Resolution | Data Format |
|---|--|---|---|
| IMERG | • 0.1°×0.1° • 90°S-90°N | 30 min (NRT)6 hr, 16 hr, & 3 month latency | |
| Combined GMI + DPR Rainfall Averages: 3-CMB | • 0.1°×0.1° • 70°S-70°N | • Monthly | HDF4NetCDFOpenDAP |
| DPR Rainfall Averages: 3-DPR | 0.25°×0.25° 5.0°×5.0° Daily: 67°S-67°N Monthly: 70°S-70°N | • Daily & Monthly | ASCII.gif, .pngKML (Google Earth) |
| GMI Rainfall Averages: 3-GPROF | • 0.25°×0.25° • 90°S-90°N | • Daily & Monthly | |

Multi-Satellite Algorithms for TRMM and GPM

http://pmm.nasa.gov/science/precipitation-algorithms

- TRMM & GPM core satellites are used to calibrate microwave observations from a constellation of national and international satellites
- Allow improved spatial and temporal coverage of precipitation data
- TRMM Multi-satellite Precipitation Analysis (TMPA)
- Widely used for applications
- TMPA will be extended to match Integrated Multi-satellitE Retrievals for GPM (IMERG)

TRMM Multi-satellite Precipitation Analysis (TMPA)


http://precip.gsfc.nasa.gov/trmm_comb.html

- TMPA combines PR & TMI rain rates
- Inter-calibrates passive rain rates from other satellite sensors
 - TMI, SSM/I (Special Sensor Microwave Imager), AMSR (Advanced Microwave Scanning Radiometer, Aqua), AMSU-B (Advanced Microwave Sounding Unit, NOAA), MHS (Microwave Humidity Sounder), IR radiometers*
- Inter-calibrates with national and international geostationary and NOAA low-earth orbiting satellites infrared measurements by using VIRS
- Final rain product is calibrated with rain gauge analyses on a monthly time scale

Integrated Multi-satellitE Retrievals for GPM (IMERG)

http://pmm.nasa.gov/sites/default/files/document_files/IMERG_ATBD_V4.5.pdf

- Conceptually similar to TMPA
- GPM constellation satellites include:
 - GCOM-W
 - DMSP
 - Megha-Tropiques
 - MetOp-B
 - NOAA-N'
 - NPP
 - NPOESS
- Final rain product is calibrated with rain gauge analyses on monthly time scale



Integrated Multi-satellitE Retrievals for GPM (IMERG)

http://pmm.nasa.gov/sites/default/files/document_files/IMERG_ATBD_V4.5.pdf

- Multiple runs accommodate different user requirements for latency and accuracy
 - "Early" now 5 hours (flash flooding) will be 4 hours
 - "Late" now 15 hours (crop forecasting) will be 12 hours
 - "Final" 3 months (research data)
- Native time intervals are half-hourly and monthly (final only)
 - Value-added products at 3 hrs, 1, 3, and 7 days .tiff will be available
 - Initial release covers 60°N-60°S will be 90°N-90°S

TMPA and IMERG

| | TMPA | IMERG |
|---------------------|----------------------|---|
| Spatial Resolution | 0.25° x 0.25° | 0.1° × 0.1° |
| Spatial Coverage | Global, 50° S – 50°N | Global, 60°S – 60°N (will be extended from pole to pole) |
| Temporal Resolution | 3 hours | 30 minutes |
| Temporal Coverage | 12/1997 – present* | 2/27/2014 – present+ |

^{*} After April 8, 2015, TRMM climatological calibration is being used to generate TMPA †TMPA and IMERG combined data will be available in early 2018 at IMERG data resolution

TRMM and GPM Data Type Convention

Learn More: https://go.nasa.gov/2y7AouZ


| Туре | Description |
|------|--|
| 1A | Instrument count, geolocated, at instantaneous field of view (IFOV) |
| 1B | Geolocated, calibrated T _b or radar power at IFOV |
| 1C | Intercalibrated brightness temperatures T _c at IFOV |
| 2A | Geolocated geophysical parameters at IFOV from a single instrument |
| 2B | Geolocated geophysical parameters at IFOV from multiple instruments |
| 3A | Space/Time averaged geophysical parameters from a single instrument |
| 3B | Space/Time averaged geophysical parameters from multiple instruments |
| 4 | Combined satellite, ground, and/or model data |

GPM File Name Convention

Learn More: https://go.nasa.gov/2y7AouZ

Level 2 File Name

2A.GPM.GMI.GPROF2008.20131101-S235152-E012400.000352.V03C.HDF5



3B-HHR.MS.MRG.3IMERG.20140805-S043000-E045959.0270.V03D.HDF5

Level 3 File Name

Trade-Offs Between Level 2 and Level 3 Precipitation Data Products

- IMERG and TMPA have lower spatial resolutions than Level 2 data
 e.g. 2A12, 2A25, 2B31, 2A-GPROF, 2A-2DPR, 2BCMB
- IMERG and TMPA have better spatial coverage with no orbit gaps compared to Level 2 and Level 3 radar, imager, and radar/imager combined data
- IMERG and TMPA:
 - are uniformly gridded
 - have uniform temporal resolution to cover diurnal variations
 - are available in multiple formats
- Used for Monitoring above and Below Normal Precipitation
- Widely Used for Applications: Flooding, Droughts, Landslides, Agriculture, and Health




TRMM and GPM Data Access and Visualization

Precipitation Data Access Tools

| Tool | Data & Format | Features |
|---|--|--|
| PPS/STORM http://storm.pps.eosdis. nasa.gov/ | Rain Rate (TRMM, GPM)HDF, PNG | Orbital and Gridded Data Search Spatial/Temporal Subsetting Individual Data and FTP Batch Download Images and Interactive Data Viewer |
| Giovanni http://giovanni.gsfc. nasa.gov/ | Rain Rate (TRMM, GPM) NetCDF, GeoTIFF, PNG, KMZ, CSV (time series only) | Spatial/Temporal Subsetting Analysis: Time-averaged maps, animation, time series, scatter plots, map correlations, vertical profiles, time-averaged differences Visualization: Maps, time series, scatter plots, histograms Near Real-Time Rain Rate Access |

Precipitation Measurement Missions


https://pmm.nasa.gov/



- Home of all information related to TRMM and GPM
- Links to data documentation and access

Precipitation Measurement Missions: Data Access

https://pmm.nasa.gov/data-access





How to Access TRMM & GPM Precipitation Data

Precipitation data from the GPM and TRMM missions is made available free to the public in a variety of formats from several sources at <u>NASA</u> Goddard Space Flight Center. This section outlines the different types of data available, the levels of processing, the sources to download the data, and some helpful tips for utilizing precipitation data in your research.

- GPM Data Downloads & Documentation
- TRMM Data Downloads & Documentation
- Explanation of GPM & TRMM Data Sources
- Data Processing "Recipes"
- · Precipitation Data in Google Earth
- · Frequency Asked Questions (FAQ)




Use of the PPS FTP and STORM requires you to first register your email address. Click here to register.

- All about TRMM and GPM data
 - Including updates, news, and FAQ
- Quick data access links and user registration



Precipitation Measurement Missions: Data Sources

http://pmm.nasa.gov/data-access/data-sources






PPS & STORM

http://storm.pps.eosdis.nasa.gov/storm

Precipitation Processing System: STORM

https://storm.pps.eosdis.nasa.gov/storm/



- All TRMM and GPM data products can be downloaded from STORM
- Data images and HDF5 data viewer are available in STORM

5/13/2016 - STORM Virtual Globe (STORM VG) and an enhanced satellite-satellite coincidence map are now available to

available in STORM.

Make faster parameter subsetting requests by using the preselected

categories available in the dropdown at the top

of the file tree interface.

Let us know if you have

any suggestions for

other categories that

would be useful.

Data Type 🕜 Algorithm 199 Satellite® Instrument @ Primary Content 1A01 @ TRMM VIRS Counts 1A11 @ TRMM TMI Counts 1A21 @ TRMM Counts 1A 1AGMI 00 GPM GMI Counts 1B 1B01 🐨 TRMM Radiance 1B TRMM TMI Brightness Temperature 1B11 @ 1B 1B21 00 TRMM PR Radar Power 1B 1BGMI 🍿 GPM GMI Brightness Temperature 1B 1BKa 😗 GPM DPR KA Radar Power 1B GPM DPR KU Radar Power 1BKu 😗

ATMS

Reflectivity

Brightness Temperature

Brightness Temperature

TRMM

GCOMW1

1C21 @

1CAMSR2 @


1CATMS @

1C

1C



Giovanni http://giovanni.gsfc.nasa.gov/



Demonstration: Data Visualization


https://pmm.nasa.gov/data-access/visualization

Data Visualization Global Viewer View the latest near-realtime GPM IMERG global precipitation datasets (30 minute, 1 day, 7 day) on an interactive 3D globe in your web browser.

CESIUM

Precipitation and Applications Viewer


View and download various precipitation and applications datasets from the past 60 days (30 minute, 1 day, 3 day, 7 day precipitation, floods nowcast, landslides nowcast). Download datasets in various popular formats (TIF, SHP, arcJSON, geoJSON, topoJSON) and learn how to directly access the data via the PMM Publisher API.



STORM Event Viewer

View 2D GMI and 3D DPR data from the latest extreme weather events on an interactive 3D globe in your web browser.


(click here for mobile version)



NASA Worldview

This tool from NASA's Earth Observing System

Data and Information System (EOSDIS) provides
the capability to interactively browse global,
full-resolution satellite imagery and then download
the underlying data, including data from the Global
Precipitation Measurement Missions.





Demonstration of STORM and Giovanni

Questions for Discussion

- 1. What are the major differences between TRMM and GPM?
- 2. Why are TMPA and IMERG used the most in applications even though their spatial resolution is lower compared to TRMM and GPM sensor data (Level-2)?
- 3. Which data access tool is for bulk data download and not for analysis or visualization?



Next
Hands-on Exercise: Precipitation Data Access &
Analysis



Extra Slides: GPM Data Validation

From https://pmm.nasa.gov/training

GPM Data Product Validation

http://pmm.nasa.gov/data-access/downloads/ground-validation/

GPM precipitation data are currently being validated with a variety of field measurements

Ground Validation Data Downloads

Ground Validation Data

GPM Ground Validation Data Homepage: http://gpm-gv.gsfc.nasa.gov/

GPM Ground Validation Data Access: https://ghrc.nsstc.nasa.gov/pub/fieldCampaigns/gpmValidation/


The goal of this site is to provide a one-stop-shopping portal for accessing the various radar, disdrometer, gauge and other instrument data sets supporting GPM GV activities. Use the tabs above to access the various datasets, including:


- Radar
- Gauge
- Disdrometer
- NOAA/NMQ
- Field Campaigns
- · Validation Network
- Wallops Precipitation Research Facility

GPM Data Product Validation

http://pmm.nasa.gov/data-access/downloads/ground-validation/


GPM precipitation data are currently being validated with a variety of field measurements





GPM and TRMM Level-2 Data Product Comparison

Higher spatial resolution, coverage, and details in GPM products




Courtesy: William Olson (PMM Investigator), NASA Mesoscale Atmospheric Processes



GPM and TRMM Level-2 Data Product Comparison

V1 (TRMM/NEXRAD based) Database




Improved coverage in GPM GMI product

Courtesy: Christian Kummerow (PMM Investigator), Colorado State University



Validation – 3-hourly, 0.25° IMERG, 3B42, MRMS for June 15, 2014

- IMERG better than 3B42 for precipitation occurrence
- IMERG performs modestly better for precipitation volume
- Note: Original footprint GPROF retrievals below 0.1 mm/hr are thresholded to zero
- How this affects IMERG depends on the resolution of the input sensor and subsequent averaging (here 0.25°)





Slide Courtesy J. Wang (SSAI; NASA/GSFC 612)




Validation – 3-hourly, CONUS-avg. IMERG, 3B42, MRMS for April – July 2014

- IMERG better for bias and RMSE
- IMERG and 3B42 trend high at high rates
- At this spatial scale, error is roughly multiplicative









Slide Courtesy J. Wang (SSAI; NASA/GSFC 612)



Validation – Snow in IMERG, NWS WSR88D, 12 March 2014

- IMERG converted to dBZ, WSR88D in dBZ; both original resolution
- Hang-back line in radar missing in IMERG
- 2-5" of snow with near-blizzard conditions at Cleveland, Ohio, ~1900 UTC








Validation – Supercells in IMERG, NWS WSR88D, July 22, 2014

- IMERG converted to dBZ, WSR88D in dBZ; both original resolution
- IMERG has good placement of supercells
- Anvils more prominent in IMERG, lower maximum values (resolution?)




Slide Courtesy of B. Rose (Weather Channel)



Validation – Daily IERG and Pocomoke Fine-Scale Grid, April-Aug 2014

- 23 surface gauges in a 6x5 km near Wallops Island, Virginia
- Excellent correlation for most events (warm season)
- Both over- and under-estimates for largest events



Slide courtesy J. Tan (UMBC; WFF)